



2.5m
POWERWATER
POWERLADDER
Series 3

WHO SAID 'SIZE MATTERS'

You can be just as effective with a short lift

*Think Safe, Work Safe!
Keep your Orchard
to a more user friendly
height, with the **NEW**
edp® 2.5m Power-Ladder*



2.5m



e-as-y as...
edp®

Best suited for close plantings

PHONE: (03) 5820 5337

PERFECT FOR PRUNING, THINNING OR PICKING

Machine Specifications

Engine:	11hp Honda GX340 SXE overhead valve petrol engine. Electric & pull start.
Hydraulic drive:	Via pump (single or double) through foot operated control valves to 2 drive wheel motors.
Wheel Drive:	6:1 reduction drive motors with free-wheeling hub and over-running valve which self brakes through hydraulics
Max. platform height:	2.5 metres (8.4') or 3.0 metres (10') or 3.5 metres (11'6") or 3.8 metres (12'6")
Overall width:	1790mm (5.11') 1870mm (6.2') 3m Model or 2187mm (7.2') 3.5 Model or 2187mm (7.2') 3.8m Model.
Weight:	780 kgs 2.5m, 780 kgs 3m Model, 825 kgs 3.5m Model, 840 kgs 3.8m Model.
Platform:	Designed for quick, easy, comfortable and safe operation. Foot controls, engine E-stop, start button, throttle control, variable ground speed switch, air outlet for pruning tools, padded picking bucket and tool box.
Foot controls:	Foot pedals give control of platform position whilst leaving hands free for the job.
Tyres:	Drive: 26 x 12.00 x 12 Supa Terra Grip 8 ply Pivot: 20.5 x 8.00 10 block 6 ply
Approvals:	Compliance with AS 1418.1 and AS 1418.10 "Boom Type Elevating Work Platform", AS 2550.10 "Safe use, Elevating work platforms".
Maximum SWL:	200 kgs
Option Features:	Planetary reduction wheel gears incorporating a "failsafe" brake.



edp australia Pty Ltd
33 - 37 O'Brien St. Mooroopna,
Victoria 3629. Tel: (03) 5820 5319
Mobile: 0418 575 369,
Fax: (03) 5825 2758,
Website: www.edp.com.au
Email: sales@edp.com.au

